




WIREWOUND ELECTRONICS PVT.LTD.

(As an ISO 9001:2015 & IATF 16949:2016)

Drum Core Inductors (10X12) With Pin



10x12 wth Pin
A = 12mm
B = 14mm
C = 8mm ± 0.5mm
D = 0.60 ± 0.1mm

SPECIAL FEATURES :

- Shrink tubing protected winding.
- Fixed lead spacing.
- Low cost.
- Wide range of inductance.
- Small mounting space required.
- The other types low DCR, large current.
- Best for power supply line.
- Vertical mount.

Sr No	SIZE	Part No	Inductance 1KHz @ 0.3V	Tolerance	Current Rating
1	10X12 WITH PIN	DI-1093	1.6uH	±20%	3A - 3.5A
2	10X12 WITH PIN	DI-1094	3.3uH	±20%	4A-5.5A
3	10X12 WITH PIN	DI-1095	4.7uH	±10%	4.4A
4	10X12 WITH PIN	DI-1096	6uH	±10%	5A
5	10X12 WITH PIN	DI-1097	10uH	±20%	5A- 6A
6	10X12 WITH PIN	DI-1098	15uH	±20%	4A
7	10X12 WITH PIN	DI-1099	33uH	±20%	4A -5.5A
8	10X12 WITH PIN	DI-1100	68uH	±10%	3 - 3.5A
9	10X12 WITH PIN	DI-1101	100uH	±10%	2A
10	10X12 WITH PIN	DI-1102	120uH	±10%	3-3.8A
11	10X12 WITH PIN	DI-1103	150uH	±10%	1A
12	10X12 WITH PIN	DI-1104	200uH	±10%	1.5A - 2A
13	10X12 WITH PIN	DI-1105	220uH	±10%	3 - 3.5A
14	10X12 WITH PIN	DI-1106	330uH	±15%	900mA - 1.2A
15	10X12 WITH PIN	DI-1107	330uH	±15%	500A
16	10X12 WITH PIN	DI-1108	525uH	±15%	900mA -1.2A
17	10X12 WITH PIN	DI-1109	900uH	±10%	700mA - 1A
18	10X12 WITH PIN	DI-1110	1mH	±10%	500 - 800mA
19	10X12 WITH PIN	DI-1111	1.5mH	±10%	500mA
20	10X12 WITH PIN	DI-1112	1.8mH	±10%	300mA
21	10X12 WITH PIN	DI-1113	2mH	±10%	500mA
22	10X12 WITH PIN	DI-1114	2.2mH	±5%	400 - 600mA
23	10X12 WITH PIN	DI-1115	2.7mH	±10%	80 -100mA
24	10X12 WITH PIN	DI-1116	4mH	±10%	300mA
25	10X12 WITH PIN	DI-1117	4.2mH	±10%	300mA
26	10X12 WITH PIN	DI-1118	10mH	±10%	300mA
27	10X12 WITH PIN	DI-1119	18mH	±10%	200mA

Power supplies.

DC-DC converters, TVS, LED drivers, computer,
Computer peripherals, home electric appliances.



Wirewound -Web- www.wirewound.in/Email Id:- wirewound@gmail.com/Mob-9822261409/7722077394